

PRESTOTIG AC/DC TIG machines are designed for the welding specialists. PRESTOTIG machines fulfill the most demanding welders needs. The rugged design and optimum performance makes these machines the ideal partner for all workshop and on-site requirements.

Specification

- Built-in cooling unit
- User-friendly front panel
- AC: adjustment of the balance cleaning time/penetration
- Complete welding cycle: pre/post. gas - up/down slope current with setting
- MMA or 2T-4T TIG modes and spot mode selection
- Pulsed and synergic pulsed TIG current.
- HF, PAC arc striking.
- Supply voltage defect indicator.
- Digital display of parameter.
- 9 Programme memory.



Technical features

PRESTOTIG 350W AC/DC	
Power supply	3~ 400 V (±10%) 50/60 Hz
No load voltage	70 V
Secondary current range	3 - 350 A (DC)
DutyCycle 10mn 40°C at 60%	350 A
DutyCycle 10mn 40°C at 100%	280 A
Tool connection	13 mm
Kind of display	Digital
Protection index	IP 23 S
Protection class	H
Dimensions (LxH) mm	690 x 260 x 870
Weight kg	74
Standard	EN 60974-1 / EN 60974-10

» Delivery equipment

5 m primary cable,
5 m earth cable & clamp and DINSE connector,
1,5 m fitted gas hose.

» Items codes

W000265132 - PRESTOTIG 350 WACDC PACK PRESTOTIG 350 WACDC 3PH-400V
W000262991 - PRESTOTIG 350W AC/DC

» Options

W000263309 - TROLLEY - ACDC>200A
W000263312 - REMOTE CONTROL RC2 5M
W000270325 - MANUAL REMOTE RC2 10M PRESTOTIG-CITOTIG-SMARTY ACDC
W000263314 - FOOT PEDAL FP2
W000010167 - FREEZCOOL 9.6L

» Associated tools

W000278404 - PROTIG NG 35W EB C5B - 5M
W000278405 - PROTIG NG 35W EB C5B - 8M
W000306444 - WEAR PARTS BOX T40-35W
W000306136 - TORCH EXTENSION W-S-5B-15M
W000260682 - WELDLINE KIT 50C50PLUS

» Environnement & protections

W000372475 - CHAMELEON 4V 2500
W000010421 - WELDING GLOVES TIG T9